

Single Number Access For Multiple Locations (formerly 4025) **

**** NOTE** - this capability was moved to the main section of the ONA Services User Guide for the July 1995 update.

Surrogate Client Number (4002)

This capability provides a method for customers of an ESP to have a "presence" in the ESP's serving office as a "virtual telephone number." This capability will allow an ESP to identify the "calling number" of customers served by central offices where demand is insufficient to justify a Foreign Central Office (FCO) arrangement for calling number identification services such as SMDI that are currently limited by technology to intraoffice applications only.

This capability is presently only feasible from 1A ESS switches. This capability cannot be used with Call Forwarding Don't Answer to a DID number. This capability is limited to intraoffice operation.

Generic Name of ONA Service	Product Name	BSE or CNS
Surrogate Client Number	BS - Surrogate Client Number	BSE

Reference: GR-581 LSSGR: Remote Call Forwarding FSD 01-02-1402 (A Module of LSSGR, FR-64), Issue 1, June 2000 (replaces TR-TSY-000581 Issue 1 – no technical changes).

This service, if offered as a BSE, is associated with the Circuit Switched Line serving arrangement.

Switched 56 Kilobit Service (3019,4021,5036)

Switched 56 Kilobit Service enables subscribers to transmit and receive data at the rate of 56 kilobits per second. Customers requiring InterLATA/Interstate transport can subscribe to an Interexchange Carrier that has Switched 56 Kilobit Service connectivity. The telephone company may offer Switched 56 Kilobit Access Service using Feature Group D protocol arrangements.

Generic Name of ONA Service	Product Name	BSE or CNS
Switched 56 Kilobit Service	BA - Switched 56 Kilobit Service	BSA
	BS - AccuPulse®	BSA
	NX - Switchway	BSA

FEATURE OPERATION:

Customers establish calls by dialing 7 or 10 digits as they would for a POTS call. Calls can only terminate to another Switched 56 line and cannot be used for normal voice communications.

TECHNOLOGICAL AND FEATURE INTERACTION CONSIDERATIONS:

1. This feature is available in the following central office switches:

Switch Type	1A ESS	5ESS
Earliest Generic Release	1AE8	5E6

2. This service is offered from specially equipped 1A ESS and 5ESS switches using facilities that are designed to accommodate 56 kilobits per second, full duplex, synchronous transmission. Remote access arrangements are available for customer locations not within the local wire center area of the specially equipped switches.
3. Subscriber loops from the local central office to customers' premises must be 4-wire, non-loaded facilities that can be designed to meet the specifications of Digital Data Service.
4. Interoffice facilities are specially equipped and are dedicated to the transport of Switched 56 Kilobit Service traffic. Access facilities are also specially equipped and dedicated to Switched 56 Kilobit Service.
5. Customers' CPE must be Accunet Compatible.

® AccuPulse is a registered service mark of BellSouth Corporation.

6. References:

- GR-334 Switched Access Service: Transmission Parameter Limits and Interface Combinations, Issue 1, June 1994 (replaces TR-NWT-000334, Issue 3).
- MDP-326-726 Digital Data System Channel Interface Specification, Issue 1, September 1983.

This service is associated with the Circuit Switched Trunk basic serving arrangement.

Third Number Billing Inhibited (4012,7067)

This capability provides Enhanced Services Providers (ESPs) with the ability to prevent third number calls from being billed to their switched access billing accounts, (e.g., DID numbers). This capability is provided by the operating procedures of a BOC providing operator services capabilities.

When a call is made to a BOC operator services system, and the caller requests the charges be billed to a third number, the operator makes a call to the third number for verification that the charges will be accepted. If no answer is received when the third number is called for verification of billing acceptance, the bill to third request is rejected.

In some areas, when a call is made to a BOC operator services system, and the caller requests the charges be billed to a third number, the operator queries the Line Information Database (LIDB) to determine the billed party's preference concerning bill to third number requests. If the information in the LIDB indicates to always reject bill to third party attempts, then the bill to third request is rejected.

Generic Name of ONA Service	Product Name	BSE or CNS
Third Number Billing Inhibited	BS - Billed Number Screening *	BSE or CNS
	SWB - Billed Number Screening	CNS

Reference: FR-271 (replaces FR-NWT-000271) Operator Service Systems Generic Requirements (OSSGR), Issue 002, February 2002. See FSD 85-01-0300 for information about Third Number Billing, see GR-1177 OSSGR: Special Billing Features (FSD 85 Series), A Module of OSSGR, FR-271 & FD-LECKIT-CD-01, Issue 1, June 1997, Issue 2 – December 2000.

* This capability is available throughout the BellSouth region upon customer request.

Three Way Calling (3020,4020,5019,8028)

Three Way Calling (TWC) allows a customer to add a third party to an existing conversation without operator assistance. The party initiating TWC may hold one party with privacy exclusion while dialing and talking with another party and can later include the held party in TWC.

Generic Name of ONA Service	Product Name	BSE or CNS
Three Way Calling	BA - Three Way Calling	BSE
	BS - Three Way Calling	CNS
	NX - 3 Way Calling	BSE
	Qwest - Three Way Calling	BSE

FEATURE OPERATION:

A customer subscribing to TWC is able to add a third party to a stable call regardless of which party originated the call. The subscribing customer flashes his switch-hook, receives recall dial tone, dials the third party, and flashes the switch-hook again. The third party may be added to the call while the station is receiving ringing or the subscribing customer may speak with the third party in private prior to adding the third party to the stable call.

The third party will be disconnected from the call if the party initiating the TWC flashes the switch-hook.

If the party initiating the TWC disconnects, all parties are disconnected.

If a party other than the party initiating the TWC disconnects, the remaining two parties may continue the call.

TECHNOLOGICAL AND FEATURE INTERACTION CONSIDERATIONS:

1. This feature is available in the following central office switches:

Switch Type	1A ESS	5ESS	DMS-100
Earliest Generic Release	1AE8	5E2	BCS17

2. Recursive use of TWC is limited only by resources of the switching system and transmission capabilities (A adds on B, B adds on C, C adds on D, etc.)
3. Dialing restrictions of a station continue in effect when dialing a party to be added on.
4. Speed Calling can be used when adding a party.
5. The initiator of TWC should not receive a Call Waiting tone. Other parties on the call can receive and respond to a Call Waiting tone.

6. Either or both legs of a three way call may be an interexchange or international call.
7. TWC is not available on lines with two or more parties.
8. References:
 - GR-577 LSSGR: Three-Way Calling, FSD 01-02-1301 (A Module of LSSGR, FR-64), Issue 1, June 2000 (replaces TR-TSY-000577 Issue 1 & Revision 1 – no technical changes).

This service, if offered as a BSE, is associated with the Circuit Switched Line serving arrangement.

Traffic Data Reports (4016,5012,8016)

This capability will provide ESPs with periodic (e.g., weekly) printed summaries of traffic data on their network facilities that are associated with central office switches. Traffic data reports include traffic information such as number of call attempts (peg count), number of blocked calls (overflow), and usage by ESP trunk group (minutes of use). The standard methods for delivering this information are paper printouts or magnetic tape in a standard format.

Generic Name of ONA Service	Product Name	BSE or CNS
Traffic Data Reports	BS - Access To Traffic Data/Network Usage Information Service	BSE
	NX - Trunk Group Measurement Reports	BSE
	Qwest - Traffic Data Report Service	BSE

References:

- TR-NWT-000335 Voice Grade Special Access Service - Transmission Parameter Limits and Interface Combinations, Issue 3, May 1993
- Also see Recommendation X.25 of the ITU-TS [formerly CCITT] Red Book.

This service, if offered as a BSE, may be associated with the Circuit Switched Line or Trunk basic serving arrangements.

Transmission Improvement for Circuit Switched Services (8012)

This capability provides the ESP with a high quality transmission line for use on local switched service. It provides transmission performance between 0 and 4 dB at 1000 Hz between the network interface at the subscriber's location and the serving central office switch.

Generic Name of ONA Service	Product Name	BSE or CNS
Transmission Improvement for Circuit Switched Services	Qwest - Improved Transmission Performance	BSE

References: GR-334 Switched Access Service: Transmission Parameter Limits and Interface Combinations, Issue 1, June 1994 (replaces TR-NWT-000334, Issue 3).

This service, if offered as a BSE, is associated with the Circuit Switched Line basic serving arrangement.

Uniform Access Numbers for Business Lines (4010)

This service provides the ESP with the capability of using a single seven digit telephone number throughout the BellSouth region, Operating Company, State, Local Access and Transport Area (LATA), or NPA. The ESP's traffic is delivered to one location per Traffic Operator Position System (TOPS) Tandem switch per LATA.

Generic Name of ONA Service	Product Name	BSE or CNS
Uniform Access Numbers for Business Lines	BS - Uniform Access Numbers	BSE

FEATURE OPERATION:

The ESP's Uniform Access Number (UAN) traffic is delivered from the originating end office to the associated TOPS Tandem switch over a dedicated trunk group. The TOPS Tandem switch provides the translation and routing functions required to support the service. The ESP's clients will dial the UAN, which will be routed to the associated TOPS Tandem switch. The TOPS Tandem switch translates the UAN and then routes the traffic to the ESP's location. The UAN service is required to support the Automatic Number Identification (ANI) and Custom Service Areas (CSA) basic service elements.

The originating end office translations are set to route the UAN traffic using a unique NXX as a trigger. The 440 NXX will serve the BellSouth region, the 530 NXX will serve South Central Bell only, and the 930 will serve Southern Bell only.

A dedicated one way trunk group from each of the TOPS Tandem switch subtending end offices is used to deliver the UAN traffic to the TOPS Tandem switch. This trunk group is designed to deliver the called number (UAN) and calling line ANI to the TOPS Tandem switch. The Operator Services Signaling (OSS) protocol is used to deliver the information over the trunk group.

The TOPS Tandem switch collects the incoming information and translates the UAN to determine how the call should be handled.

The UAN calls can be delivered to the ESP either through the normal circuit switched network or using dedicated trunks from the TOPS to the ESP's location. If ANI delivery is desired, the trunk side option is required.

At the present time, this service will only be offered to ESPs through the General Subscriber Services Tariff (GSST).

References: not available

This service, if offered as a BSE, is associated with the Circuit Switched Line or Circuit Switched Trunk basic serving arrangements.

3. Appendix 1 - Region Specific Services - Technical Descriptions for Packet Switched Access Arrangements

Abbreviated Call - Packet (8036)

This capability allows the customer to access predefined addresses by utilizing a predesignated unique alphanumeric character(s) in lieu of the normal call initiation process. The port is not limited to sole access of the predefined address when normal call initiation procedures are followed.

Generic Name of ONA Service	Product Name	BSE or CNS
Abbreviated Call - Packet	Qwest - Abbreviated Call - Packet	CNS

Default Window Size - Packet (5022,8007)

This permits the customer to select a nonstandard default window size of three in one or both directions of transmission. If nonstandard default window sizes are not selected, the default window size of two will apply to both directions of transmission. Default window sizes are set at subscription time.

Generic Name of ONA Service	Product Name	BSE or CNS
Default Window Size - Packet	NX - Default Window Size	BSE or CNS
	Qwest - Nonstandard Window Size - Packet	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service is associated with the Packet Switched X.25 and X.75 basic serving arrangements.

Flow Control Parameter Negotiation - Packet (8003)

Flow control allows the data receiver to limit the rate at which it accepts data by controlling the window size and maximum packet size for each direction of transmission. Negotiation is done on a per call basis during the call setup.

Generic Name of ONA Service	Product Name	BSE or CNS
Flow Control Parameter Negotiation - Packet	Qwest - Flow Control Parameters (Packet)	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service, if offered as a BSE, is associated with the Packet Switched X.25 and X.75 basic serving arrangements.

Incoming Calls Barred - Packet (5024,8001)

Incoming Calls Barred allows the customer the option to prevent incoming virtual circuit calls from being sent to their data terminal equipment (DTE). When used in conjunction with a Closed User Group (CUG) this feature prevents individual members of the CUG from receiving calls from outside of the CUG. This option will allow call origination only.

Generic Name of ONA Service	Product Name	BSE or CNS
Incoming Calls Barred - Packet	NX - Incoming Calls Barred	BSE or CNS
	Qwest - CUG Incoming Access Barred (Packet)	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service, if offered as a BSE, is associated with the Packet Switched X.25 and X.75 basic serving arrangements.

Logical Channels - Packet (8005)

Logical Channels capability allows the data terminal equipment (DTE) to derive multiple logical channels from a single physical access line. This is accomplished by specifying the logical channel number on every packet which crosses the network interface.

Generic Name of ONA Service	Product Name	BSE or CNS
Logical Channels - Packet	Qwest - Logical Channel (Packet)	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service, if offered as a BSE, is associated with the Packet Switched X.25 and X.75 basic serving arrangements.

Logical Channel Layout - Packet (8004)

This capability permits the arrangement of logical channels to be configured as incoming, outgoing, two way and/or private virtual circuit. The logical channel layout is established at subscription time.

Generic Name of ONA Service	Product Name	BSE or CNS
Logical Channel Layout - Packet	Qwest - Logical Channel Layout (Packet)	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service, if offered as a BSE, is associated with the Packet Switched X.25 and X.75 basic serving arrangements.

Menu Server - Packet (7000)

This service is no longer offered by Southwestern Bell.

Multiple Network Addresses/Port - Packet (3001,5027,8006)

This capability allows more than one network address to be assigned to a single access port. Multiple addresses can be purchased in blocks, up to a maximum number of 1000. Messages are delivered according to predetermined customer specifications.

Generic Name of ONA Service	Product Name	BSE or CNS
Multiple Network Addresses/Port	BA - Multiple Network Addresses (Packet)	BSE
	NX - Multiple Network Addresses/Port	BSE or CNS
	Qwest - Multiple Network Addresses (Packet)	BSE

Reference: Bell Atlantic Technical Reference 72211, Interface Specification for the Bell Atlantic Public Data Network, Issue C, December 1991.

This service, if offered as a BSE, is associated with the Packet Switched X.25 basic serving arrangement.

Outgoing Calls Barred (5028,8002)

This capability allows the customer the option to prohibit outgoing virtual calls for their data terminal equipment (DTE). When used in conjunction with a Closed User Group (CUG) this feature prevents individual members of the CUG from establishing calls outside of the CUG. This option will allow the receipt of incoming virtual circuit calls only.

Generic Name of ONA Service	Product Name	BSE or CNS
Outgoing Calls Barred - Packet	NX - Outgoing Calls Barred	BSE or CNS
	Qwest - CUG Outgoing Access Barred (Packet)	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service, if offered as a BSE, is associated with the Packet Switched X.25 and X.75 basic serving arrangements.

Permanent Virtual Circuit - Packet (5029,8008)

Permanent virtual circuits are the electronic equivalent of a private line between two points. At the customer's option, a virtual circuit is established between two customer data terminal locations (DTEs) within the network on a dedicated basis. These two locations are electronically connected, operating similar to a private line between the two points. The association between the two DTEs is established via service provisioning.

Generic Name of ONA Service	Product Name	BSE or CNS
Permanent Virtual Circuit - Packet	NX - Permanent Virtual Circuit	BSE or CNS
	Qwest - Permanent Virtual Circuit (Packet)	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service, if offered as a BSE, is associated with the Packet Switched X.25 and X.75 basic serving arrangements.

Reverse Charge Request Option (Packet) (5030,8009)

Reverse charging allows the originating user to request that the call be charged to the called party during call setup. The reverse charging call request is delivered to the called party only when their data terminal equipment (DTE) is configured for Reverse Charge Acceptance. If the terminating DTE does not subscribe to Reverse Charge Acceptance, the call will be cleared.

Generic Name of ONA Service	Product Name	BSE or CNS
Reverse Charge Request Option (Packet)	NX - Reverse Charge Request	BSE or CNS
	Qwest - Reverse Charge Option (Packet)	BSE

Reference: GR-301 Public Packet Switched Network Generic Requirements (PPSNGR), Issue 2, December 1997 (replaces TR-TSY-301, Issue 2).

This service, if offered as a BSE, is associated with the Packet Switched X.25 basic serving arrangement.

4. Appendix 1 - Region Specific Services - Technical Descriptions for Dedicated Access Arrangements

Access To Customer Premises Announcement (5035)

This feature allows an ESP to furnish customized announcement services to an Automated Call Distribution customer. ACPA connects callers in the ACD queue to customer provided announcements or music. Using this feature the ESP can provide and manage announcements on behalf of the customer. The ESP requires private line access for each ACPA arrangement.

Generic Name of ONA Service	Product Name	BSE or CNS
Access To Customer Premises Announcements	NX - Customized Announcement Service	BSE

FEATURE OPERATION:

The ESP furnishes an announcement to the ACPA port over a private line. The ACD will automatically connect a caller in queue to the ACPA port when the feature is present.

TECHNOLOGICAL AND FEATURE INTERACTION CONSIDERATIONS:

1. This feature is available in the following central office switches:

Switch Type	DMS-100
Earliest Generic Release	BCS36

2. This is a feature of Automatic Call Distribution.

Access To Order Entry System (4004)

This capability will allow ESPs to provide basic ordering information to the business office through a mechanized interface.

Generic Name of ONA Service	Product Name	BSE or CNS
Access To Order Entry System	BS - Administrative Management Service (AMS)	BSE or CNS

FEATURE OPERATION:

A new offering, currently using the BellSouth project name of Administrative Management Service (AMS), will provide a mechanized interface for customers to provide service ordering information to the appropriate business office.

This service will be offered on a dial-up or dedicated basis. The ESPs will not have direct access to the Order Entry System, but will have access through the AMS front-end processor. The front-end processor will provide the necessary security and information screening.

References: not available.

This service, if offered as a BSE, is associated with the Access To Operations Support Systems Information BSE (which is associated with the Dedicated Digital (< 64 kbps) basic serving arrangement).

ADSL Service (4032)

ADSL Service is an interstate data access service that allows Internet Service Providers (ISPs) or Network Service Providers (NSPs) to provide service to their customer(s) using Asymmetric Digital Subscriber Line technology. This capability allows ISPs/NSPs to establish a point-to-point virtual circuit between an end user premises location and another location designated by the subscribing ISP/NSP. ADSL Service allows downstream speeds from 192 Kbps to 6.0 Mbps and upstream speeds from 192 Kbps to 640 Kbps. ADSL Service requires ATM switch connectivity between the ATM switch and the ISP's/NSP's designated location.

Generic Name of ONA Service	Product Name	BSE or CNS
ADSL Service	BS – BellSouth ADSL Service	BSE

DS0-B Subrate Multiplexing Service (4015)

DS0-B Subrate Multiplexer (SRM) service provides time division multiplexing of multiple client digital derived data channels into a single standard interface for efficient interconnection to an ESP.

Generic Name of ONA Service	Product Name	BSE or CNS
DS0-B Subrate Multiplexing Service	BS - DS0-B Interface	BSE or CNS

FEATURE OPERATION:

Service is established via a service order placed by the ESP with the local operating company. Appropriate dedicated transport facilities (including local channel and applicable interoffice mileage elements) are also ordered for access to the SRM. The ESP negotiates and makes arrangements with its clients to connect their individual derived data channels to the SRM. These orders must be coordinated with the ESP in order to ensure adequate facilities are available and appropriate channel assignments, as specified by the ESP, are made.

TECHNOLOGICAL AND FEATURE INTERACTION CONSIDERATIONS:

1. This capability is independent of central office switch type.
2. The DS0-B SRM is interconnected to the ESP's client via an appropriate derived data channel service in the local serving office.
3. The ESP interconnects to the DS0-B SRM via an appropriate four-wire dedicated transport facility.
4. The DS0-B signal is a standard DDS signal as specified in Technical Advisory TA-TSY-00280.

References:

See BellSouth documents TR73548 "Derived Channel Access Service Digital Data Over Voice Network Interface Specifications", Issue 1 June 1990 and Addendum 1 March 1991.

This service, if offered as a BSE, is associated with the Dedicated Derived Channel BSA.